



**International  
Components  
Corporation**

1337 Lincoln Avenue  
Suite 5  
Holbrook, NY 11741  
Ph: (631) 952 - 9595 Fax:  
E-mail: oemsales@icc107.com

## ELECTRO-ACOUSTIC TRANSDUCER

Contact Us



Product: ELECTRO-ACOUSTIC TRANSDUCER

Description: Sealed For Flow Solder And Washing, Low Frequency

Part Number: BRT2513P-06

### SPECIFICATIONS

#### CIRCUIT

Without Circuit

COIL IMPEDANCE

38 ohm

COIL RESISTANCE

$27 \pm 4$  ohm

FRAME DEPTH

12.5 mm

FRAME DIAMETER

24.7 mm

MAX CURRENT

80 mA

MOUNTING DIMENSIONS

10.2 mm

OPERATING TEMPERATURE

-40 TO +85°C

OPERATING VOLTAGE

3 ~ 5 vdc

RATED VOLTAGE

5 vdc

RESONANT FREQUENCY

730 Hz

ROHS COMPLAINT

YES

SOUND LEVEL OUTPUT

85dB @ 10 cm

TERMINAL TYPE

2 Pins

1337 Lincoln Avenue Suite 5 Holbrook, NY 11741 , Telephone: (631) 952 - 9595, Fax: