



**International
Components
Corporation**

1337 Lincoln Avenue
Suite 5
Holbrook, NY 11741
Ph: (631) 952 - 9595 Fax:
E-mail: oemsales@icc107.com

ELECTRO-ACOUSTIC TRANSDUCER

Contact Us



Product: ELECTRO-ACOUSTIC TRANSDUCER

Description: Sealed For Flow Solder And Washing, Low Frequency

Part Number: BRT2513P-12-S

SPECIFICATIONS

| | |
|-----------------------|-----------------|
| CIRCUIT | Without Circuit |
| COIL IMPEDANCE | 115 ohm |
| COIL RESISTANCE | 120 ± 15 ohm |
| FRAME DEPTH | 12.5 mm |
| FRAME DIAMETER | 24.7 mm |
| MAX CURRENT | 55 mA |
| MOUNTING DIMENSIONS | 10.2 mm |
| OPERATING TEMPERATURE | -40 TO +85°C |
| OPERATING VOLTAGE | 8 ~ 14 vdc |
| RATED VOLTAGE | 12 vdc |
| RESONANT FREQUENCY | 1000 ~ 1500 Hz |
| ROHS COMPLAINT | YES |
| SOUND LEVEL OUTPUT | 85dB @ 10 cm |
| TERMINAL TYPE | 2 Pins |

1337 Lincoln Avenue Suite 5 Holbrook, NY 11741 , Telephone: (631) 952 - 9595, Fax: