



**International  
Components  
Corporation**

1337 Lincoln Avenue  
Suite 5  
Holbrook, NY 11741  
Ph: (631) 952 - 9595 Fax:  
E-mail: oemsales@icc107.com

## SHIELDED LOW LEAKAGE OVAL SPEAKER

Contact Us



Product: SHIELDED LOW LEAKAGE OVAL SPEAKER

Description: These Speakers Are Available, On A Special Order Basis, In 4, 16, 32, 45 And 100 Ohms.

Part Number: S20X35VFS-5W

### SPECIFICATIONS

FRAME DEPTH	39.0 mm
FRAME DIAMETER	50.0 x 90.0 mm
FREQUENCY RESPONSE	Fo ~ 15000
MATERIAL CONE/FRAME	PAPER / METAL
MEAN VALUE AT	0.6, 0.8, 1.0, 1.2KHz
MEASURED AT	1.0 W @ 0.5M
OUTPUT SOUND PRESSURE LEVEL (S.P.L)	86 ± 3 dB
RATED POWER WATTS Nom/Max	5.00 / 8.00
RESONANT FREQUENCY HZ WITOUT BAFFLE	240 ± 20%
ROHS COMPLAINT	YES
VOICE COIL IMPEDANCE	8 ± 15% @ 1.0KHz

1337 Lincoln Avenue Suite 5 Holbrook, NY 11741 , Telephone: (631) 952 - 9595, Fax: